

PEEL-OFF

SAFETY DATASHEET

Section 1 – IDENTIFICATION

PRODUCT INFORMATION

Product Name : PEEL-OFF

Molecular Weight : Not Applicable

COMPANY IDENTIFICATION

Company : HHC INDUSTRIES SDN BHD

Address : No 234, Jalan KIP 7, Taman Perindustrian KIP, 52200 Kuala Lumpur.

Tel : 6017-572 5883

Emergency number: +6017-5725883(Simon Lim) Email: sales.hcindustries@gmail.com

Section 2 – HAZARDS IDENTIFICATION

WARNING STATEMENT:

NONE CONSIDERED NECESSARY

PRECAUTIONARY MEASURES:

Avoid eye contact.

Use appropriate personal protective equipment.

FIRST AID:


Eye Contact: Remove contact lenses if worn. Flush thoroughly with water.

Skin Contact: Wash contact area with soap and water.

Ingestion: Seek immediate medical attention. Do not induce vomiting.

Inhalation: Seek medical attention if coughing or respiratory discomfort occurs

This product contains no hazardous materials.



Section 3 – COMPOSITION/INFORMATION ON INGREDIENT

Substance/Mixture : Mixture, Methyl Palmatite Intermediate 50-60%

Other means of identification : Not Available

CAS number : Not Available

Chemical Formula : Nano Palmitic saturated C16, C15H31COOCH3 mixture

PEEL-OFF

SAFETY DATASHEET

Section 4 – FIRST AID MEASURES

POTENTIAL HEALTH EFFECTS

INHALATION

- Negligible unless heated to produce vapors. Vapors or finely misted materials may irritate the mucous membranes and cause irritation, dizziness, and nausea. Remove to fresh air.

EYE CONTACT

- May cause irritation. Irrigate eye with water for at least 15 to 20 minutes. Seek medical attention if symptoms persist.

SKIN CONTACT

- Prolonged or repeated contact is not likely to cause significant skin irritation. Material is sometimes encountered at elevated temperatures. Thermal burns are possible.

INGESTION

- No hazards anticipated from ingestion incidental to industrial exposure.

EYES

- Irrigate eyes with a heavy stream of water for at least 15 to 20 minutes.

SKIN

- Wash exposed areas of the body with soap and water.

INHALATION

- Remove from area of exposure, seek medical attention if symptoms persist.

INGESTION

- Give one or two glasses of water to drink. If gastro-intestinal symptoms develop, consult medical personnel. (Never give anything by mouth to an unconscious person.)

Section 5 – FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Dry chemical, foam, halon, CO₂, water spray (fog). Water stream may splash the burning liquid and spread fire.

SPECIAL FIRE FIGHTING PROCEDURES

- Use water spray to cool drums exposed to fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS

- Oil soaked rags can cause spontaneous combustion if not handled properly. Before disposal, wash rags with soap and water and dry in well ventilated area.
- Firefighters should use self-contained breathing apparatus to avoid exposure to smoke and vapor.

DATE OF ISSUE: 22th AUGUST 2016,

Version: 1

Previous revision: NIL

PEEL-OFF

SAFETY DATASHEET

Section 6 – ACCIDENTAL RELEASE MEASURES

- Remove sources of ignition, contain spill to smallest area possible. Stop leak if possible.
- Pick up small spills with absorbent materials such as paper towels, "Oil Dry", sand or dirt.
- Recover large spills for salvage or disposal.
- Wash hard surfaces with safety solvent or detergent to remove remaining oil film. Greasy nature will result in a slippery surface.

Section 7 – HANDLING AND STORAGE

- Store in closed containers between 50° F and 120° F (10° C and 50° C)
- Keep away from oxidizing agents, excessive heat, and ignition sources.
- Store and use in well ventilated areas.
- Do not store or use near heat, spark, or flame, store out of sun.
- Do not puncture, drag, or slide this container.
- Drum is not a pressure vessel; never use pressure to empty.

Section 8 – EXPOSURE CONTROL /PERSONAL PROTECTION

RESPIRATORY PROTECTION

- If vapors or mists are generated, wear a NIOSH approved organic vapor/mist respirator.

PROTECTIVE CLOTHING

- Safety glasses, goggles, or face shield recommended to protect eyes from mists or splashing.

PVC coated gloves recommended to prevent skin contact.

OTHER PROTECTIVE MEASURES

- Employees must practice good personal hygiene, washing exposed areas of skin several times daily and laundering contaminated clothing before re-use.

Section 9 – PHYSICAL/CHEMICAL PROPERTIES

Boiling Point	: 760 mm Hg:>200°C
Volatiles,% by Volume	: <2
Flash Point (ASTM 93)	: over 316° c
Flammability Limits	: None known
Specific Gravity (H2 O=1)	: 0.921
Solubility in H2 O, % by Volume	: partially misible
Vapor Pressure, mm Hg	: <2
Evaporation Rate, Butyl Acetate=1	: <1
Vapor Density, Air=1	:>1
Appearance and Odor	: orange liquid, mild odor. pH: 5.5

DATE OF ISSUE: 22th AUGUST 2016,

Version: 1

Previous revision: NIL

Section 10 – STABILITY AND REACTIVITY

GENERAL

- This product is stable and hazardous polymerization will not occur.

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID

- Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS

- Combustion produces carbon monoxide, carbon dioxide along with thick smoke.

Section 11 – TOXICOLOGI INFORMATION

SHORT TERM EXPOSURE

- Route of entry : Eye Contact, Skin Contact, Inhalation, Ingestion
- Acute effect eye contact : Low order of toxicity
- Acute effect skin contact : Low order of toxicity
- Acute effect inhalation : Low order of toxicity
- Acute effect ingestion : No Hazard in normal industrial use

LONG TERM EXPOSURE

- Effect of chronic exposure : None
- Target organ : None

SPECIAL HEALTH EFFECCTS

- Carcinogen (OSHA guidelines) : No

PRODUCT TOXICOLOGI

- Oran toxicity : Low order of toxicity
- Dermal toxicity : Low order of toxicity
- Inhalation toxicity : Not noted

Section 12 – ECOLOGICAL INFORMATION

BIODEGRADABLE

Section 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

- Waste may be disposed of by a licensed waste disposal company. Contaminated absorbent material may be disposed of in an approved landfill.
- Follow local, state and federal disposal regulations.

PEEL-OFF

SAFETY DATASHEET

Section 14 - TRANSPORTATION INFORMATION

Hazard class : None
Shipping name : PEEL-OFF
Label information : Listed on labels are the Product Name, Batch Number & Net Weight
HS Code : 3402900090

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: IATA, IMDG

Section 15 – REGULATORY INFORMATION

Section 312 Extremely Hazardous Substances : None
Section 311/312 Hazard Categories : Non hazardous
Section 313 Toxic Chemicals : Non Toxic

Section 16 – OTHER INFORMATION

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is to the best of the company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy,